

**Amendment to the Abstract:**

The Abstract has been amended. A revised Abstract is attached.

**ABSTRACT**

A valve plate includes a plurality of suction holes and a plurality of suction reed valves for opening and closing them. At least two of ~~theses~~these suction reed valves have different natural frequencies. In this configuration, a natural frequency of one reed valve is larger. Therefore, even when an operation frequency is changed to a higher frequency, the compressor can suck a refrigerant gas into a cylinder efficiently without occurring delayed closing and reduction of a lift amount. Thus, refrigerating capacity and compression efficiency can be increased.

Respectfully submitted,

  
Lawrence E. Ashery, Reg. No. 34,515  
Attorney for Applicant

LEA/fp

Attachment: Abstract

Dated: January 27, 2005

P.O. Box 980  
Valley Forge, PA 19482-0980  
(610) 407-0700

The Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. **18-0350** of any fees associated with this communication.

**EXPRESS MAIL: Mailing Label Number: EV 447 718 957 US**

**Date of Deposit: January 27, 2005**

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

  
KATHLEEN LIBBY

Application No.:

To Be Assigned

10/522514

MAT-8651US

DT01 Rec'd PCT/PTC 27 JAN 2005

ABSTRACT

A valve plate includes a plurality of suction holes and a plurality of suction reed valves for opening and closing them. At least two of these suction reed valves have different natural frequencies. In this configuration, a natural frequency of one reed valve is larger. Therefore, even when an operation frequency is changed to a higher frequency, the compressor can suck a refrigerant gas into a cylinder efficiently without occurring delayed closing and reduction of a lift amount. Thus, refrigerating capacity and compression efficiency can be increased.